Spectral Fractal Dimension

JÓZSEF BERKE

Department of Statistics and Information Technology University of Veszprém, Georgikon Faculty of Agronomy H-8360 Keszthely, Deák Ferenc street. 57. HUNGARY

berke@georgikon.hu http://www.georgikon.hu/digkep/berkea.htm

Abstract: - There were great expectations in the 1980s in connection with the practical applications of mathematical processes which were built mainly upon fractal dimension mathematical basis. Results were achieved in the first times in several fields: examination of material structure, simulation of chaotic phenomena (earthquake, tornado), modelling real processes with the help of information technology equipment, the definition of length of rivers or riverbanks. Significant results were achieved in practical applications later in the fields of information technology, certain image processing areas, data compression, and computer classification. In the present publication the so far well known algorithms calculating fractal dimension in a simple way will be introduced as well as the new mathematical concept named by the author 'spectral fractal dimension', the algorithm derived from this concept and the possibilities of their practical usage.

Key-Words: - Image Processing, Fractal Dimension, Spectral Fractal Dimension

1 Introduction

In the IT-aimed research-developments of present days there are more and more processes that derive from fractals, programs containing fractal based algorithms as well as their practical results. Our topic is the introduction of ways of application of fractal dimension, together with the mathematical extension of fractal dimension, the description of a new algorithm based on the mathematical concept, and the introduction of its practical applications.

2 The fractal dimension

Fractal dimension is a mathematical concept which belongs to fractional dimensions. Among the first mathematical descriptions of self similar formations can be found von Koch's descriptions of snowflake curves (around 1904) [14]. With the help of fractal dimension it can be defined how irregular a fractal curve is. In general, lines are one dimensioned, surfaces are two dimensioned and bodies are three dimensioned. Let us take a very irregular curve however which wanders to and from on a surface (e.g. a sheet of paper) or in the three dimension space. In practice [1], [2], [3], [4] [8], [9], [10], [11], [12], [13], [14], [15] we know several curves like this: the roots of plants, the branches of trees, the branching network of blood vessels in the human body, the lymphatic system, a network of roads etc. Thus, irregularity can also be considered as the extension of the concept of dimension. The dimension of an irregular curve is between 1 and 2, that of an irregular surface is between 2 and 3. The dimension of a fractal curve is a number that characterises how the distance grows between two given points of the curve while increasing resolution. That is, while the topological dimension of lines and surfaces is always 1 or 2, fractal dimension can also be in between. Real life curves and surfaces are not real fractals, they derive from processes that can form configurations only in a given measure. Thus dimension can change together with resolution. This change can help us characterize the processes that created them.

The definition of a fractal, according to Mandelbrot is as follows: A fractal is by definition a set for which the Hausdorff-Besicovitch dimension strictly exceeds the topological dimension [12].

The theoretical determination of the fractal dimension [1]: Let (X,d) be a complete metric space. Let $A \in H(X)$. Let $N(\varepsilon)$ denote the minimum number of balls of radius ε needed to cover A. If

$$FD = \lim_{\varepsilon \to 0} \left\{ Sup \left\{ \frac{LnN(\varepsilon)}{Ln(1/\varepsilon)} : \varepsilon \in (0,\varepsilon) \right\} \right\}$$
 (1)

exists, then FD is called the fractal dimension of A. The general measurable definition of fractal dimension (FD) is as follows:

$$FD = \frac{\log \frac{L_2}{L_1}}{\log \frac{S_1}{S_2}} \tag{2}$$

where L_1 and L_2 are the measured length on the curve, S_1 and S_2 are the size of the used scales (that is, resolution). There have been several methods developed that are suitable for computing fractal dimension as well. [14] - Table 1.

2.1 Measuring fractal dimension

Fractal dimension, which can be the characteristic measurement of mainly the structure of an object in a digital image [15], [12], [4], [1], can be computed applying the Box counting as follows:

- 1. Segmentation of image
- 2. Halving the image along vertical and horizontal symmetry axis
- 3. Examination of valuable pixels in the box
- 4. Saving the number of boxes with valuable pixels
- 5. Repeat 2-4 until shorter side is only 1 pixel

To compute dimension, the general definition can be applied to the measured data like a function (number of valuable pixels in proportion to the total number of boxes).

Methods	Main facts	
Least Squares Approximation	theoretical	
Walking-Divider	practical to length	
Box Counting	most popular	
Prism Counting	for a one dimensional	
	signals	
Epsilon-Blanket	to curve	
Perimeter-Area relationship	to classify different types	
	images	
Fractional Brownian Motion	similar box counting	
Power Spectrum	digital fractal signals	
Hybrid Methods	calculate the fractal	
	dimension of 2D using	
	1D methods	

 Table 1 Methods of Computing Fractal Dimensions




Fig.1 The fractal dimension measured with the help of the Box counting of the two images is the same (FD=1.99), although the two images are different in shades of colour.

3 Spectral fractal dimension

Nearly all of the methods in Table 1 measure structure. Neither the methods in Table 1 nor the definition and process described above gives (enough) information on the (fractal) characteristics of colours, or shades of colours. Figure 1 bellow gives an example.

Measuring with the help of the Box counting the image on the right and the one on the left have the same fractal dimension (FD=1.99) although the one on the left is a black and white (8 bit) image whereas the other one on the right is a 24-bit coloured image containing shades as well - the original images can be found at www.georgikon.hu/digkep/sfd/index.htm, [16] -, so there is obviously a significant difference in the information they contain. How could the difference between the two images be proven using measurement on the digital images? Let spectral fractal dimension (SFD) be:

$$SFD = \frac{\log \frac{L_{S2}}{L_{S1}}}{\log \frac{S_{S1}}{S_{S2}}}$$
 (3)

where L_{S1} and L_{S2} are measured spectral length on N-dimension colour space, S_{S1} and S_{S2} are spectral metrics (spectral resolution of the image).

In practice, $N=\{1, 3, 4, 6, 32, 79\}$, where

- N=1 black and white or greyscale image,
- N=3 RGB, YCC, HSB, IHS colour space image,
- N=4 traditional colour printer CMYK space image
- N=6 photo printer CC_pMM_pYK space image or Landsat ETM satellite image
- N=32 DAIS7915 VIS_NIR or DAIS7915 SWIP-2 sensors
- N=79 DAIS7915 all



In practice the measure of spectral resolution can be equalled with the information theory concept of $\{S_i=1, \ldots, S_i=16, \text{ where } i=1 \text{ or } i=2\}$ bits.

Typical spectral resolution:

- Threshold image -1 bit
- Greyscale image 2-16 bits
- Colour image 8-16 bits/bands

On this basis, spectral computing is as follows:

- 1. Identify which colour space the digital image is
- 2. Establish spectral histogram in the above space
- 3. Half the image as spectral axis
- 4. Examine valuable pixels in the given N-dimension space part (N-dimension spectral box)
- 5. Save the number of the spectral boxes that contain valuable pixels
- 6. Repeat steps 3-5 until one (the shortest) spectral side is only one (bit).

In order to compute dimension, the definition of spectral fractal dimension can be applied to the measured data like a function (number of valuable spectral boxes in proportion to the whole number of boxes), computing with simple mathematical average as follows:

$$SFD_{measured} = \frac{3 \times \sum_{j=1}^{N-1} \frac{\log(BM_j)}{\log(BT_j)}}{N-1}$$
(4)

where

- BM_j number of spectral boxes containing valuable pixels in case of i-bits
- BT_j total number of possible spectral boxes in case of j-bits

During computing:

- 1. Establish the logarithm of the ratio of BM/BT to each spectral halving
- 2. Multiply the gained values with N (index of dimension)
- 3. Find the mathematical average of the previously gained values

On this basis, the measured SFD of the two images introduced in figure 1 show an unambiguous difference (SFD_{left side image}=1.21, SFD_{right side image}=2.49).

4 Practical Application of the Algorithm

A computer program that measures SFD parameter has been developed in order to apply the algorithm above. The measuring program built on this method has been developed in two environments (MS .NET, C++). According to the measurements so far it can be stated that there is no significant difference between the computing times of the algorithm running in either environment (in case of P4, 2,6GHz, 512 MB RAM it is nearly around half a minute in both cases a 3 Mpixels image). This means that the algorithm can be applied

well in object oriented programming environments as well

Practical testing has been completed using images where the expected (theoretical) measurement results are unambiguous - Table 2.

Type of images	Theoretical SFD	Measured SFD
3 image bands, intensity of every pixel is zero - black coloured 3-band image	0	0
3 image bands, intensity of every pixel is 255 - white- coloured 3 band image	0	0
3 image bands, intensity of every pixel is the same, different from zero and 255 - one colour 3-band image)	0	0

Table 2 SFD measurement results of test images

The SFD results measured by the program are invariant for identical scale pixels with different geometric positions in case the number of certain scales is the same and shade of colour is constant.

Successful practical application of SFD at present [4], [5], [6], [7]:

- Measurement of spectral characteristics of satellite images
- Psychovisual examination of image compressing methods
- Qualification of potato seed and chips
- Temporal examination of damage of plant parts
- Classification
- Virtual Reality based 3D terrain simulation

Image	FD	SFD	SFD
		average	minimum
Fig. 1. left	1,99	1,21	0,14
Fig. 1. right	1,99	2,49	2,40
Sunset	2,00	2,31	2,29
Sunset thresold 64	1,87	0,37	0,14
Tatika	2,00	2,68	2,55
Tatika plant	1,99	2,66	2,48
Tatika plant green	1,99	2,52	2,36
Tatika plant flower	1,99	2,49	2,30

Table 3 Fractal Dimension and Spectral Fractal Dimension of some images [16]

5 Conclusion

When examining digital images where scales can be of great importance (image compressing, psychovisual examinations, printing, chromatic examinations etc.) SFD is suggested to be taken among the so far usual (eg.

sign/noise, intensity, size, resolution) types of parameters (eg. compression, general characterization of images). Useful information on structure as well as shades can be obtained applying the two parameters together.

Several basic image data (aerial and space photographs) consisting of more than three bands are being used in practice. There are hardly any accepted parameters to characterize them together. I think SFD can perfectly be used to characterize (multi-, hyper spectral) images that consist of more than three bands.

On the basis of present and previous measurements it can be stated that SFD and FD are significant parameters in the classification of digital images as well.

SFD can be an important and digitally easily measurable parameter of natural processes and spatial structures besides the structural parameters used so far. These measurements are being carried out at present already using the above method applicable in practice - and are to be accessed by anyone [16].

The applied method has proven that with certain generalization of the Box method fractal dimension based measurements – choosing appropriate measuresgive practically applicable results in case of optional number of dimension.

References:

- [1] Barnsley, M. F., *Fractals everywhere*, Academic Press, 1998.
- [2] Barnsley, M. F. and Hurd, L. P., *Fractal image compression*, AK Peters, Ltd., Wellesley, Massachusetts, 1993.
- [3] Batty, M. and Longley, P. *Fractal cities*, Academic Press, 1994.
- [4] Berke, J., Fractal dimension on image processing, 4th KEPAF Conference on Image Analysis and Pattern Recognition, Vol.4, 2004, pp.20.
- [5] Berke, J., Real 3D terrain simulation in agriculture, *1st Central European International Multimedia and Virtual Reality Conference*, Vol.1, 2004, pp.195-201.
- [6] Berke, J., The Structure of dimensions: A revolution of dimensions (classical and fractal) in education and science, 5th International Conference for History of Science in Science Education, July 12 16, 2004.
- [7] Berke, J. and Busznyák, J., Psychovisual Comparison of Image Compressing Methods for Multifunctional Development under Laboratory Circumstances, WSEAS Transactions on Communications, Vol.3, 2004, pp.161-166.
- [8] Burrough, P.A., Fractal dimensions of landscapes and other environmental data, *Nature*, Vol.294, 1981, pp. 240-242.
- [9] Buttenfield, B., Treatment of the cartographic line, *Cartographica*, Vol.22, 1985, pp.1-26.

- [10] Encarnacao, J. L. Peitgen, H.-O. Sakas, G. Englert, G. eds. Fractal geometry and computer graphics, Springer-Verlag, Berlin Heidelberg 1992.
- [11] Lovejoy, S., Area-perimeter relation for rain and cloud areas, *Science*, Vol.216, 1982, pp.185-187.
- [12] Mandelbrot, B. B., *The fractal geometry of nature*, W.H. Freeman and Company, New York, 1983.
- [13] Peitgen, H-O. and Saupe, D. eds. The Science of fractal images, Springer-Verlag, New York, 1988.
- [14] Turner, M. T., Blackledge, J. M. Andrews, P. R., *Fractal Geometry in Digital Imaging*, Academic Press, 1998.
- [15] Voss, R., Random fractals: Characterisation and measurement, Plenum, New York, 1985.
- [16] Authors Internet site of parameter SFD www.georgikon.hu/digkep/sfd/index.htm.